

10-16 x 1-1/2" HWH with Bonded Washer Teks®

Buildex # 1308000

Distributed by:

MasonAccess.com
(800) 924-6802



Product Name: Climaseal®

Description: Climaseal is a high quality metal filled thermoset coating. Climaseal has been uniquely formulated to react and form a complete long life protection to provide the optimum in corrosion resistance properties. Climaseal is self sacrificing to the base substrate if penetrated or damaged. Fasteners coated with Climaseal exhibit excellent resistance to most forms of abrasion and torque.

Chemical Identification: Organic Metallic Polymer

Color: Silver/Metallic Grey

Cure: Thermoset

Typical Film Properties:

Humidity Resistance Excellent
Solvent Resistance Excellent
Impact Resistance Excellent
UV Resistance Excellent

Fastener: TEKS / Maxiseal / SCOTS

Base Treatment: Zinc (non-electrolytically applied)

Film Climaseal - Metal filled (Aluminum)

Thermo-set Polyester

Test Method: Salt Spray, ASTM B117

1000 Hours -10% or less red rust

Kesternich, DIN50018, 2.0L 30 Cycles- 10% or less red rust

Pull-Out Data (Average Lbs. Ultimate)

Steel	22 ga.	20 ga.	18 ga.	16 ga.	14 ga.	12 ga.
Thickness	.030"	.036"	.048"	.060"	.075"	.105"
	266	299	499	708	967	1474

Fastener Values

Tensile	Shear	Torsional		
	Avg. Ultimate	Strength		
1936 lbs.	1400 lbs.	61 in/lbs.		

Typical Use:

Attaching Brick Veneer Anchors

Teks and Climaseal are Trade Marks of ITW Buildex And Illinois Tool Works, Inc.