



PRODUCT SUBMITTAL



SureTie WS Anchoring System Thermal

Designed with a Wide Slot to accept the #4515 SureTie WS Adjustable Double Hook



“SureTie fasteners do not create any significant thermal bridging effects on the wall system.”

Test Results Available Upon Request

MATERIAL CONFORMANCE	SIZES / FINISHES
<p>ASTM A1064/A1064M, A82 / A82M - (Cold drawn steel wire) Tensile Strength - 80,000 psi Yield Point - 70,000 psi</p> <p>ACI / ASCE 530 - (Building code requirements for masonry structures)</p> <p>Mill Galvanized / Zinc Coating: ASTM A641 / A641M (0.10 Oz per sq ft)</p> <p>Hot Dip Galvanized after fabrication / Zinc Coating ASTM A153 / A153M-B2 (1.50 oz per sq ft)</p> <p>Stainless Steel ASTM 580 / ASTM 580M Type 304 (Type 316 available on special order)</p>	<p># 4522 SureTie WS Silver-gray climaseal finish resulted in 0% red rust at 1000 hours exposure to ASTM B-117 salt spray testing.</p> <p>Insulation: 1" 1-1/2" 2" 2-1/2" 3" 3-1/2" 4" 4-1/2"</p> <p>Wallboard 5/8" 1/2"</p> <p># 4515 SureTie Double Hook 3/16" dia. 3" 4" 5"</p> <p>FINISH : (Sure Tie Hook) Mill Galvanized Hot Dip Galvanized Stainless Steel</p>
<p>Recycled Content: Mill Galvanized & Hot Dipped, 82.8% Post-Consumer 17% Post Industrial / Pre-Consumer,</p> <p>Stainless Steel, 60% Post Consumer V O C Content - 0%</p>	



Distributed by:
MasonAccess.com
(800) 924-6802