







Brick

Block

Stone

Mixing Instructions:

- Start Mixer
- Add at least 1/2 to 2/3 of the total water to be used
- Add Easy-Spred®
- Allow Easy-Spred® to mix for 60 to 90 seconds
- Add remaining ingredtents in the usual or specified manner
- Mix until the material has the desired consistancy

Note: A mixing time of 6 minutes is recommended

Key Benefits:

- Improves workability
- Improves board life
- High compression and bond strength
- Reduces early stage shrinkage
- Reduces efflorescence
- Great flow and pumpability
- Enhances color performance
- User friendly
- Saves money

www.casy-spred.com

Field Prepared Type M Mortar:

- 2 x 94# bags of Portland cement
- 1 x 7# bag of Easy-Spred®
- 6 cubic feet of sand

Field Prepared Type & Mortar:

- 2 x 94# bags of Portland cement
- 1 x 7# bag of Easy-Spred®
- 9 cubic feet of sand

Field Prepared Type N Mortar:

- 1 x 94# bag of Portland cement
- 1 x 7# bag of Easy-Spred®
- 6 cubic feet of sand

Admixture Dosage Rate:

- 2% by cement weight


Easy-Spred® benefits almost any cementitious environent and has performed in mortars and grouts since the 1950's. Easy-Spred® is used as an admixture to improve the field performance and hardened properties of cementitious materials and also as a code recognized lime replacement. Easy-Spred® is recognized for use in all seismic zones by the International Building Codes.

Peninsula Products, Inc. 3014 W. Palmira Ave. Suite 200 Tampa, FL 33629

Office: 813.832.4080 Fax: 813.832.4202

Email: info@easy-spred.com

"The Miracle in Mortar"®









Brick

Block

Stone











