

# PRODUCT SUBMITTAL



## Aqua Flash Latex Primer



**USE:** AQUA FLASH Latex Primer is a one component water-base high tack primer specifically designed to promote maximum adhesion of the AQUA FLASH waterproofing membranes on all vertical and horizontal surfaces.

### GENERAL INSTRUCTIONS:

Before using this product read the Material Safety Data Sheet (MSDS) for more detailed information. MSDS is available from FIBERWEB.

### APPLICATION INSTRUCTIONS:

Apply by spray or with a soft bristled brush to all surfaces in an even coat at 50 square feet per gallon. At 75 F. allow primer to dry 4-8 hrs or until surface of primer is slightly tacky to dry but doesn't transfer when touched. If AQUA FLASH membrane is not applied within the dry time, re-prime. Apply only when air/surface temperature is above 45 degrees F.

**DISPOSAL:** Empty container may retain vapor and product residue. Do not cut or weld on or near this container. For industrial use only Use only according to directions.

**STORAGE:** Store at above freezing temperatures. Do not allow to freeze

### KEEP FROM FREEZING

Health	1
Flammability	0
Reactivity	0

### CAUTION: Statement of Hazards:

Will cause eye irritation. May cause skin irritation with repeated or pro-contact. Inhalation of vapors may cause headaches, dizziness, nausea and irritation to nose, throat and lungs.

### PRECAUTIONS TO TAKE:

**Keep away from children.** Use adequate ventilation. Keep container closed. Do not take internally. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Avoid breathing vapors.

### PROTECTIVE EQUIPMENT:

Wear recommended protective gloves and safety glasses. If exposure exceeds TLV wear NIOSH/MSHA approved respirator.

**FIRST AID: EYES:** Flush with water for at least 15 minutes. Get medical attention.

**SKIN:** Wash immediately with soap and water. Remove contaminated clothing. -wash before use

**INGESTION:** Get medical aid. Do not induce vomiting.

**For emergency, health and safety information call- 781-461-1946**

**WARNING: Under poorly ventilated conditions or confined space appropriate OSHA procedures must be followed.**

Seller makes no warranty expressed or implied as to the merchantability, fitness for any particular-purpose or any other incidental or consequential damages. Since conditions of use are beyond seller's control, buyer assumes all risk of use of this product. Seller's sole obligation shall be to replace product if found to be defective.

**SPECIFICATIONS:** Meets ASTM D-1227-82 Type III

**PHYSICAL CHARACTERISTICS:**

Weight/gallon ( approx)	9 lbs.
Total Solids	49 Wt%
Consistency	Brush or Spray
Flammability	
Wet	Non flammable
Dry	Dried Film after exposure to Bunsen flame for 3 minutes will Show self extinguishing properties in 1 minute
Clean Up	
Wet	Water and Soap
Dry	Mineral Spirits



**Corporate Office:** 400 Roundtree Rd Charlotte, NC 28217  
TEL: (800) 849-6722 FAX: (704) 525-3761

**Mailing Address:** P.O. Box 240988 Charlotte, NC 28224



[www.wirebond.com](http://www.wirebond.com)

**Memphis Plant:** 2365 Harbor Ave. Memphis, TN 38113  
TEL: (800) 441-8359 FAX: (901) 775-9449

**Mailing Address:** P.O. Box 13124 Memphis, TN 38113