

HOHMANN & BARNARD, INC.

Corporate Headquarters: 30 Rasons Court • Hauppauge, NY 11788 toll free: 800.645.0616 • fax: 631.234.0683

BRANCH OFFICES: ALABAMA • ILLINOIS • MARYLAND • NEW YORK • PENNSYLVANIA • TEXAS • CANADA

LEED Material Information

Date:	
Submittal Register Number:	

General Product Information Product Cor

Product:				Product	Location of Extraction	Mileage to Jobsite	% Weight ⁵
Manufacturer:				Component	of Raw Materials ⁴	3003.60	3 1
Supplier:							
Total Product Cost:							
			<u> </u>				
Project Information	on						
Project Name:							
Location:	USA	CANADA					
Subcontractor:							
					1		

^{*}Note 1: VOC Content required for adhesives, sealants, paints, and coatings.

Notes

THIS CERTIFICATION BECOMES NULL & VOID IF THE PRODUCTS LISTED ABOVE ARE NOT PURCHASED THROUGH HOHMANN & BARNARD, INC.

Subcontractor Certification

Product Specific Information

Location of Manufacture (City/State): 2

% Pre-Consumer Recycled Content

% Post-Consumer Recycled Content

FSC Chain-of-Custody Certification No.

Supporting Document Type Attached ³

VOC Content (q/L) '

Mileage To Jobsite:

We herby certify that the material information contained herein is an accurate representation of the material qualifications to be provided by us, as components of the final building construction. Furthermore, we understand that any change in such qualifications during the purchasing period will require prior written approval from the Construction Manager and the Owner.				
Reviewed By:	Date:			

^{*}Note 2: "Manufacture" refers to the final assembly of components into the building product that is furnished and installed by tradesmen. For example, if the hardware comes from Dallas, TX; the lumber from Keene, NH; and the joist is assembled in Syracuse, NY; then the location of Manufacture is Syracuse, NY.

^{*}Note 3: Examples of supporting document types include "Cut sheet," "Letter from manufacturer," or "Product literature."

^{*}Note 4: This information to be provided for any product manufactured (See Note 2) within 500 miles of jobsite.

^{*}Note 5: % Weight = (Weight of Component / Weight of Product) 100