

Core Lock Single Rebar Positioner



**MATERIAL CONFORMANCE**


Wire (Carbon Steel): Prefabricated from cold-drawn steel wire conforming to **ASTM A1064/A1064M, ASTM A82/ A82M**  
 Tensile Strength - 80,000 p.s.i. | Yield Point - 70,000 p.s.i. minimum

**ASTM A951/A951M** (Standard Specification for Steel Wire for Masonry Joint Reinforcement)

**ACI / ASCE 530** (Building Code Requirements for Masonry Structures)  
 Hot-Dip Galvanized after fabrication: **ASTM A153/A153M-B2 (1.5 oz/ft)**

Wire (Stainless Steel): **ASTM A580/ASTM 580M - AISI Type 304**  
 (Type 316 available on special orders)

**Recycled Content:**  
 Hot Dipped,  
 82.8% Post-Consumer  
 17% Post Industrial / Pre - Consumer  
 Stainless Steel,  
 97% Pre-Consumer  
 V O C Content - 0%



**DESCRIPTION / SIZES / FINISHES**

**DESCRIPTION:**

- CoreLock is installed 1-1/4" deep into the CMU instead of on top of the block.
- Diagonal positioning in the core ensures that rebar is always centered automatically and prevents any movement.
- Does not interfere with installation of wire reinforcement.
- One piece design with no welds.
- Safety bend ensures correct installation.

**SIZES:**

6" Single	8" Single	10" Single	12" Single
-----------	-----------	------------	------------

**FINISHES:** Mill Galvanized    Hot Dip Galvanized