PRODUCT DATA SHEET

Stone Anchors – Split Tail

Sample Sizes

Field Bend to Fit

USES:

- Tying to CMU, concrete, steel or wood
- Useful on veneers, composites, coping

ADVANTAGES:

- Simple and economical to use
- Will not corrode in contact with limestone
- Extremely long life

DIMENSIONS:

☑ Standard 1/8” thick x 1-1/4” wide x Length to suit with 3/4" Split Tail

- Stock Lengths: 1-1/2”, 2”, 2-1/2”, 3”, 3-1/2”, 4”, 4-1/2”, 5”, 5-1/2”, 6” & 8”

☐ Other thicknesses (3/16”, 1/4"...), widths & lengths available

FINISHES:

☐ Stainless Steel - Type 304 – *Natural Stone*
ASTM A666, ASTM A480/A480M and ASTM A240/A240M

☐ Hot Dip Galvanized after fabrication/ Zinc Coating – *Precast or Cast Stone*
ASTM A153/A153M-B2 (1.50 oz. per sq ft)

☐ Powder Coated Stainless

For technical assistance contact us at 1-800-924-6802 or sales@masonaccess.com

Distributed by:
Masonry Accessories, Inc.
MasonAccess.com
1-800-924-6802
sales@masonaccess.com